

DUO



Elegant 4 and 6 inch Up and Down Luminaire
Clean aesthetics, no power cord and uncompromised function

DUO is Meteor Lighting's latest Up and Down pendant that is a direct solution to the increasing need for indirect ceiling lighting in a variety of project applications. With more and more architectural designs focusing more on ceiling space, Meteor sought to develop a sleek fixture with perfect optics and high functionality.

DUO is cable-free and has no power cable attachment to the fixture. The power supply is directly attached to the less than 1 inch canopy, aesthetically hidden away for a minimalistic design. The entire fixture is then powered using a High Lumen Power Suspension System, making it not only extremely safe but simply beautiful to look at.



This fixture is also highly versatile with an uplight lumen output range of 1,500 – 2,400 lm and downlight lumen output range of 1,500 – 6,500 lm as well as uplight beam angles of 35° – 100° and downlight beam angles from 15° to 100°.



Available in a range of dimming capabilities, this flexibility does not compromise the look and feel of the luminaire, and is done through a hidden signal wire that can also offer separate up and downlight dimming controls.



Available in a range of dimming capabilities:
SPV, DMX, TRIAC, ECO, 3-WIRE

DUO Product Video
<https://youtu.be/ObPdYu9CBQI>



DUO 4 Specification

Wattage (Uplight / Downlight)	30W(15W / 15W)	50W(25W / 25W)	75W(25W / 50W)
Dimension	Ø4.8" X 15.1"		
Total Lumen Output	3000 lm	4410 lm	6510 lm
Lumen (Uplight)	1500 lm	2205 lm	2205 lm
Lumen (Downlight)	1500 lm	2205 lm	4305 lm
Color Temp	2700K, 3000K, 3500K, 4000K		
Beam Angle (Downlight)	15°, 25°, 35°, 60°, 100°(with diffuser)		
Beam Angle (Uplight)	35°, 60°, 100°(with diffuser)		
Dimming	Superior 0-10V DMX TRIAC 3-wire ECOsysteM	<1% <0.1% <1% (120V only) <1% (UNV only) <1% (UNV only)	

DUO 6 Specification

Wattage (Uplight / Downlight)	30W(15W / 15W)	50W(25W / 25W)	75W(25W / 50W)	95W(25W / 70W)
Dimension	Ø6.4" X 20"			
Total Lumen Output	2800 lm	4670 lm	7005 lm	8810 lm
Lumen (Uplight)	1500 lm	2335 lm	2335 lm	2335 lm
Lumen (Downlight)	1500 lm	2335 lm	4305 lm	6475 lm
Color Temp	2700K, 3000K, 3500K, 4000K			
Beam Angle (Downlight)	40°, 60°, 100°(with diffuser)			
Beam Angle (Uplight)	40°, 60°, 100°(with diffuser)			
Dimming	Superior 0-10V DMX TRIAC 3-wire ECOsysteM	<1% <0.1% <1% (120V only) <1% (UNV only) <1% (UNV only)		